





ElaTherm 4202


thermal insulation




breathable



water resistant



elastic




light



Description Designed for *interior lining* of hiking, winter, work footwear, is made of synthetic microfibers and microspheres. Particularly suitable for shoes with C.I. certification (Cold Insulance). The typical softness allows it to be used with all shape of footwear. . Easy to work and cut without fraying.

Characteristics Air is one of the best thermal insulators, which in breathable materials is subject to convection currents and thus to be replaced by cold air. The present technologies make it possible to reduce this effect, thus improving the thermal insulation, using microfibers that create a dense mesh in order to slow down the transfer of the air outside. The **ElaTherm** technology combines microfibers to the microspheres, which are internally empty. The air inside the microspheres cannot get out of the material and therefore produces a thermos effect that raises the power of **thermal insulation**. The **breathability** is guaranteed by the porous fibers structures. **Lightness** and **elasticity** are a consequence of the compressibility and elastic effect of the microspheres. The **water resistant** treatment allows to preserve over time the thermal insulation preventing moisture absorption. Everything for improved comfort.

static air
dynamic air



microfiber
microsphere



Composition 61% Polyester; 39% Synthetic Resin ;

| TEST | | UNITS | STANDARD | TYPICAL VALUES |
|--------------------|-----|--------------------|-------------------|----------------|
| Weight | | gr/m ² | UNI EN ISO 2286-2 | 180 |
| Thickness | | mm | UNI ISO 2589 | 3,30 |
| Density | | gr/dm ³ | | 55 |
| Roll width | | cm | | 150 |
| Static Air | | % | | 16 |
| Dynamic Air | | % | | 84 |
| Thermal Insulation | Rct | m ² K/W | EN 31092 | 0,10 |
| | Clo | | | 0,65 |

Technical Indication
Temperatures above 130 ° C can damage the product.

ElaTherm 4202